

# Machinery



Machine type	Clamping force (kN)	Number of core puller	Mould alignment in (mm)	Screw Ø (mm)	Max. injection pressure (bar)	Max. injection speed (mm/s)	Injection weight PS (gr.)	Clearance distance holm (mm)	Min./Max daylight of tool (mm)	Max. distance plates (mm)
<b>Demag System 60</b> - Bladder accumulator - Sprue puller - Needle shut off control, hydr. & pneum. - Babyplast controller	600	2	125	30	1995	610	94	420	250 / -	700
<b>Demag Ergotech 80</b> Needle shut off control, pneum.	800	1	125	35	2387	108	157	400	250 / -	700
<b>Demag System 110</b> - Bladder accumulator - Needle shut off control, hydr. & pneum.	1100	2	125	40	2420	610	208	470	250 / -	850
<b>Demag System 250</b> - Bladder accumulator - Needle shut off control, hydr. & pneum. - CNC-handling robot - Knee lever	2750	2	160	60	1905	452	690	630	330 / 710	1385
<b>Kraus Maffei KM 110</b> - Bladder accumulator - Needle shut off control, hydr. & pneum..	1100	2	IS: 120 ES: 140	35	2500	300	142	470	300	900

- Tempering units up to 140 ° C
- Plastic dryer
- Service department for maintenance and repairs